

WHAT IS CLAIMED IS:

1 1. An apparatus for positioning a sensing head relative to a
2 workpiece, the apparatus comprising:
3 a control unit operative to provide a plurality of control signals to
4 iteratively control positioning of the sensing head relative to the workpiece;
5 a plurality of air injectors disposed and fixedly connected on the periphery
6 of the sensing head, the air injectors receiving the control signals and ejecting a gas
7 between the sensing head and the workpiece to create an air bearing and affect
8 positioning of the sensing head relative to the workpiece in response to the control
9 signals; and

10 a plurality of sensors providing a plurality of feedback signals to the
11 control unit, the feedback signals containing information relating to positioning of the
12 optical imaging sensing head relative to the workpiece.

13 2. The apparatus of claim 1, wherein the control unit is further
14 operative to map readings received from the sensors from a sensor-space representation to
15 a virtual-sensor-space representation before forming an output-to-movement relationship
16 such that an inverse of an output-to-movement relationship is more likely to be
17 obtainable.

18 3. The apparatus of claim 1 further comprising:
19 a support member connected with the sensing head, the support member
20 substantially restricting movement of the sensing head to (a) translational movement
21 along a z-axis, (b) rotational movement about an x-axis normal to the z-axis, and (c)
22 rotational movement about a y-axis normal to the z-axis.

23 4. An apparatus for positioning a sensing head relative to a
24 workpiece, the apparatus comprising:
25 a plurality of first air injectors fixedly connected with the sensing head;
26 a plurality of second air injectors fixedly connected with the sensing head;
27 a plurality of sensors providing a plurality of feedback signals to the
28 control unit, the feedback signals containing information relating to positioning of the
29 sensing head relative to the workpiece; and

8 a control unit receiving the plurality of feedback signals from the sensors
9 and controlling the first and second air injectors, the control unit capable of bringing
10 positioning of the sensing head relative to the workpiece within a desired range by
11 iteratively adjusting the first air injectors, the control unit being capable of adding an
12 additional separation distance to positioning of the sensing head relative to the workpiece
13 by operating the second air injectors.

1 5. An apparatus for positioning a sensing head relative to a
2 workpiece, the apparatus comprising:

3 a plurality of sensors operative to detect a reading of positioning of the
4 sensing head relative to the workpiece;

5 a plurality of air injectors fixedly connected with the sensing head, each of
6 the air injectors capable of ejecting a gas with a variably controllable output level
7 between the sensing head and the workpiece in order to affect positioning of the sensing
8 head relative to the workpiece; and

9 a control unit operative to receive the reading from the sensors and to
10 control the air injectors, the control unit being capable of locating the sensing head
11 relative to the workpiece within a desired range, said locating comprising:

12 (a) varying the output level of each air injector by a small amount and
13 noting a resulting change in the reading received from the sensors in order to form an
14 output-to-movement relationship;

15 (b) applying an inverse of the output-to-movement relationship to the
16 reading received from the sensors in order to calculate a plurality of output adjustments;

17 (c) adjusting the output levels of the air injectors by the output
18 adjustments; and

19 (d) repeating (a) through (c) until positioning of the sensing head relative
20 to the workpiece is within the desired range.

1 6. The apparatus of claim 5, wherein the control unit is further
2 operative to map the reading received from the sensors from a sensor-space representation
3 to a virtual-sensor-space representation before forming the output-to-movement
4 relationship such that the inverse of the output-to-movement relationship is more likely to
5 be obtainable.

1 7. The apparatus of claim 5 further comprising:

2 a support member connected with the sensing head, the support member
3 substantially restricting movement of the sensing head to (a) translational movement
4 along a z-axis, (b) rotational movement about an x-axis normal to the z-axis, and (c)
5 rotational movement about a y-axis normal to the z-axis

1 8. The apparatus of claim 7, wherein the support member is a
2 cantilever spring.

1 9. The apparatus of claim 5, wherein the gas that is ejected between
2 the sensing head and the workpiece is air.

1 10. The apparatus of claim 5, wherein the air injectors are fixedly
2 connected with the sensing head at asymmetrical locations juxtaposed to the sensing
3 head.

1 11. The apparatus of claim 5, wherein the air injectors are fixedly
2 connected with the sensing head at locations juxtaposed to a perimeter portion of the
3 sensing head.

1 12. The apparatus of claim 5, further comprising a plurality of
2 additional air injectors fixedly connected with the sensing head, the additional air
3 injectors capable of ejecting gas between the sensing head and the workpiece in order to
4 add an additional separation distance to positioning of the sensing head relative to the
5 workpiece.

1 13. The apparatus of claim 5, wherein a filler material is disposed as a
2 seal between the sensing head and the air injectors to eliminate air leakage paths between
3 the sensing head and the air injectors.

1 14. A method for positioning a sensing head relative to a workpiece,
2 the method comprising the steps of:

3 detecting, using a plurality of sensors, a reading of positioning of the
4 sensing head relative to the workpiece;

5 ejecting from a plurality of air injectors fixedly connected with the sensing
6 head a gas between the sensing head and the workpiece in order to affect positioning of
7 the sensing head relative to the workpiece; and

8 locating the sensing head relative to the workpiece within a desired range,
9 said locating comprising:

10 (a) varying the output level of each air injector by a small amount and
11 noting a resulting change in the reading received from the sensors in order to form an
12 output-to-movement relationship;

13 (b) applying an inverse of the output-to-movement relationship to the
14 reading received from the sensors in order to calculate a plurality of output adjustments;

15 (c) adjusting the output levels of the air injectors by the output
16 adjustments; and

17 (d) repeating (a) through (c) until positioning of the sensing head relative
18 to the workpiece is within the desired range.

19 15. The method of claim 14, further comprising the step of mapping
20 the reading received from the sensors from a sensor-space representation to a virtual-
21 sensor-space representation before forming the output-to-movement relationship such that
22 the inverse of the output-to-movement relationship is more likely to be obtainable.

23 16. The method of claim 14, further comprising the step of
24 substantially restricting movement of the sensing head to (a) translational movement
25 along a z-axis, (b) rotational movement about an x-axis normal to the z-axis, and (c)
26 rotational movement about a y-axis normal to the z-axis

27 17. The method of claim 14, wherein the gas that is ejected between
28 the sensing head and the workpiece is air.

29 18. The method of claim 14, wherein the air injectors are fixedly
30 connected with the sensing head at asymmetrical locations juxtaposed to the sensing
31 head.

32 19. The method of claim 14, wherein the air injectors are fixedly
33 connected with the sensing head at locations juxtaposed to a perimeter portion of the
34 sensing head.

35 20. The method of claim 14, further comprising the step of ejecting
36 from a plurality of additional air injectors fixedly connected with the sensing head gas

3 between the sensing head and the workpiece in order to add an additional separation
4 distance to positioning of the sensing head relative to the workpiece.

1 21. A system for positioning a sensing head relative to a workpiece, the
2 system comprising:

3 means for detecting a reading of positioning of the sensing head relative to
4 the workpiece using a plurality of sensors;

5 means for ejecting from a plurality of air injectors fixedly connected with
6 the sensing head a gas between the sensing head and the workpiece in order to affect
7 positioning of the sensing head relative to the workpiece; and

8 means for locating the sensing head relative to the workpiece within a
9 desired range, said locating comprising:

10 (a) varying the output level of each air injector by a small amount and
11 noting a resulting change in the reading received from the sensors in order to form an
12 output-to-movement relationship;

13 (b) applying an inverse of the output-to-movement relationship to the
14 reading received from the sensors in order to calculate a plurality of output adjustments;

15 (c) adjusting the output levels of the air injectors by the output
16 adjustments; and

17 (d) repeating (a) through (c) until positioning of the sensing head relative
18 to the workpiece is within the desired range.

1 22. The system of claim 21, further comprising means for mapping
2 readings received from the sensors from a sensor-space representation to a virtual-sensor-
3 space representation before forming the output-to-movement relationship such that the
4 inverse of the output-to-movement relationship is more likely to be obtainable.

1 23. The system of claim 21, further comprising means for substantially
2 restricting movement of the sensing head to (a) translational movement along a z-axis, (b)
3 rotational movement about an x-axis normal to the z-axis, and (c) rotational movement
4 about a y-axis normal to the z-axis

1 24. The system of claim 21, wherein the gas that is ejected between the
2 sensing head and the workpiece is air.

1 25. The system of claim 21, wherein the air injectors are fixedly
2 connected with the sensing head at asymmetrical locations juxtaposed to the sensing
3 head.

1 26. The system of claim 21, wherein the air injectors are fixedly
2 connected with the sensing head at locations juxtaposed to a perimeter portion of the
3 sensing head.

1 27. The system of claim 21, further comprising:
2 means for ejecting from a plurality of additional air injectors fixedly
3 connected with the sensing head gas between the sensing head and the workpiece in order
4 to add an additional separation distance to positioning of the sensing head relative to the
5 workpiece.

105150 5023300